

SL 505



EASY CLEAN



PHTALATES FREE



LEATHER TOUCH



ELASTICITY



FIRE RETARDANT
BS 5852 Part 10-1 &
CAL TB 117 &
EN 1021 Part 1-2



SOFT TOUCH



ABRASION
RESISTANCE



AZO DYE FREE

Composición Composition Composition		77% PES - 22% EPU - 1% SILICONE	
Ancho Width Laize		140 cm	
Peso Weight Poids		420 g/m²	
Rapport Repeat Rapport	Ancho Width Laize	Liso - Plain	
	Largo Length Longueur	Liso - Plain	
Martindale UNE-EN ISO 12947 - BS 2543		80.000	
Solidez a la luz Fastness to light Résistance à la lumière ISO 105-B02		5	
Solidez al agua clorada Fastness to chlorinated water Résistance à l'eau chlorée		-	
Solidez al agua de mar Fastness to sea water Résistance à l'eau de mer		-	
Resistencia a la flexión Flexural strength Résistance a la flexion		100.000	
Solidez al frote Fastness to rubbing Résistance au frottement	Seco Dry Sec	5	
	Húmedo Wet Humide	5	
Orientación Orientation Orientation			
Aplicaciones Application Application		 TAPIZADOS DECORACIÓN	
Acabado Finish Finition		Tratamiento tacto suave Soft touch finish Doux au toucher	
Recomendaciones Recommendations Recommandations		 No exponer directamente a la luz solar. Do not expose to direct sunlight. Para su limpieza, emplear un suave paño humedecido en agua jabonosa. Use a soft cloth dampened in soapy water for its cleaning. No utilizar disolventes, lejía o detergentes agresivos. El jabón debe ser neutro. Do not use solvents, bleach or harsh detergents. Soap must be natural.	
Instrucciones de lavado Care instructions Entretien			
 No lavar Do not wash Ne pas laver  No blanquear (lejía / alternativos) Do not bleach (bleach / alternativos) Ne pas blanchir (lejía / alternativos)  No secar en secadora Do not tumble dry Ne pas sécher au sèche-linge  No planchar Do not iron Ne pas repasser  No limpiar en seco Do not dry clean Ne pas laver à sec			





15



03



04



06



50



05



22



28



27



09



19



99



01