

SL 253

INDOOR FABRIC

INFORMACIÓN GENERAL

General information / Informations générales

Composición <i>Composition</i>	%	31%PES, 40%VISCOOSA, 17%LINO, 12%CO
Ancho <i>Width</i> <i>Largueur</i>	cm	140
Masa superficial <i>Weight</i> <i>Masse</i>	g/m ²	411±5

ENSAYOS DE LABORATORIO

Tests results / Test de laboratoire

Resistencia de costuras <i>Seam strength</i> <i>Résistance de la couture</i>	mm	3,5 (Urdimbre/Warp/Chaine) – 2,3 (Trama/Weft/Trame)	
Resistencia a la abrasión <i>Abrasion resistance</i> <i>Résistance à l'abrasion</i>	Nº ciclos No. Cycles Non Cycles	45.000	
Resistencia al pilling <i>Pilling resistance</i> <i>Pilling résistance</i>	Grado Degree Degré	4-5	
Solidez al frote <i>Rubbing fastness</i> <i>Solidité au frottement</i>	Seco/Dry/Sécher		Húmedo/Wet/Humide
	Solidez/fastness/solidité	5	5
	Descarga/Discharge/Décharger	5	5

SÍMBOLOS DE CONSERVACIÓN

Care instructions / Instructions d'entretien

